



MOBILE CRUSHING & MOBILE SCREENING

Saray Mah. Keresteciler San. Sit. Keresteciler Bulv.

No:36/B 06980 Kazan-ANKARA-TURKEY

T: +90 312 815 14 59-60 F: +90 312 815 14 39

E-mail: info@evortle.com Web: www.evortle.com



BEYER MOBILE SCREENING PLANT

Type: BM 3515-R

The plant consists of the following parts:

a) Feeding Hopper

- ✓ Volume : approx. 6 m³
- ✓ Feeding Width : 4.500 mm
- ✓ Feeding Height : 4.500 mm

b) Sloped Tilting Grid

- ✓ Grid Interval : 90 mm
- ✓ Remote controlled hydraulic sloped (15°) tilting grid
- ✓ Vibro-motor

c) Dosage Belt Conveyor

- ✓ Belt Width : 1.000 mm, plain belt
- ✓ Axle Distance : 2.650 mm

Note: The machine in the picture may have optional accessories, so there may be differences from standard machine.



- ✓ Drive : 4.0 kW Gear Box Motor
- ✓ Frequency Inverter (Speed adjustable main belt conveyor)
- ✓ Rubberized Drive Drum

d) Main Belt Conveyor

- ✓ Belt Width : 1.000 mm, plain belt
- ✓ Axle Distance : 6.250 mm
- ✓ Drive : 7.5 kW Gear Box Motor
- ✓ Rubberized Drive Drum
- ✓ Side Protective Sheet Metal and Rubber

e) BEYER Special Screening Machine

- ✓ Dimension : 3.5x1.5 m/ 2 Decks;
- ✓ Capacity : max. 130 m³/h
- ✓ Drive : 7.5 kW E-Motor
- ✓ Forced vibratory, eccentric mile, 4 housings
- ✓ Top Screen Wire : 30 mm square mesh (According to customer desire)
- ✓ Bottom Screen Wire : 15 mm square mesh (According to customer desire)

f) Belt Conveyor for Fine Material

- ✓ Belt Width : 650 mm, plain belt
- ✓ Axle Distance : 7.000 mm
- ✓ Discharge Height : 3.600 mm
- ✓ Drive : 3.0 kW Drum Motor
- ✓ Hydraulic collapsible during transportation.

g) Belt Conveyor for Middle-Size Material

- ✓ Belt Width : 650 mm, herring-bone
- ✓ Axle Distance : 7.000 mm
- ✓ Discharge Height : 3.450 mm
- ✓ Drive : 3.0 kW Drum Motor
- ✓ Hydraulic collapsible during transportation.

h) Belt Conveyor for Over-Size Material

- ✓ Belt Width : 650 mm, herring-bone
- ✓ Axle Distance : 7.000 mm
- ✓ Discharge Height : 3.450 mm
- ✓ Drive : 3.0 kW Drum Motor
- ✓ Hydraulic collapsible during transportation.

i) Control Panel

Note: Evortle reserves the right to change the technical specifications of the products without any notification.



- ✓ Includes all components to operate the machine.

j) Chassis

- ✓ Tandem Axle chassis with air brakes
- ✓ King Pin and Taillights