



EREL04 Electric Wheel Loader Specification

Performance	Rated Load (t)		0.4
	Bucket rated capacity (m) ³		0.2
	Dumping height (mm) (at 45°)		1350
	Lifting Height (mm)		2100
	Dumping Reach (mm)		450
	Max. Lifting weight (kg)		500
	Max. Excavation Force (kn)		8
	Max. Grade ability		15
	Max. Turning Angel		28°±1
	Swing degree of the rear axle		3
Dimensions. &.Weight	Overall length (Bucket on Ground position) mm		2900
	Bucket width (overall width)		900
	Overall Height(mm)		2070
	Wheel base(mm)		1387
	Min Ground Clearance(mm)		300
	Net Weight (kg)		1000kg
Battery	Battery Model No.		6-EVF-120A
	rated capacity (3hr)		120Ah
	No.of battery groups		5
	Rated Voltage		60V
	Working hours (h)		4
Transmission System	Hydraulic System	Motor No.	HL-60
		Voltage	60V
		Power	1200W
		Displacement (ml/r)	14
	Tyres	Type	6.00-12
		working pressure (mpa)	0.25

EVERUN WE RUN TOGETHER WITH YOU!

Qingdao Everun Machinery Co.,Ltd

Adress: Room 902, Yongxin International Finance Centre, No.6 Qingling Road, Qingdao, China
Tel : 0086-532-80997859 Website : www.everun.cc Facebook : everunmachinery
Fax : 0086-532-80993178 Email : info@everun.cc Youtube : everunmachinery



		Qty	4
Steering System	Type of Steering Hydraulic System	Full Hydraulic Steering System	
	System Pressure (mpa)	16	
	Type of Steering Pump	External Gear Pump	
	Steering Cylinder Bore (mm)	50	
	Qty (pc)	1	
Braking System	Service Brake	Drum Brake	
	Brake Drum (mm)	200	
	Parking Brake	Drum Brake	
	Distribution Valve	Model	DL10
		Type	Triple valve stem
	Dumping Cylinder-Bore	ø50	
	Lifting Cylinder-Bore	ø50	
	Oil Capacity	Hydraulic Oil Tank (L)	11
Brake Fluid (L)		0.8	

EVERUN WE RUN TOGETHER WITH YOU!

Qingdao Everun Machinery Co.,Ltd

Address: Room 902, Yongxin International Finance Centre, No.6 Qingling Road, Qingdao, China
 Tel : 0086-532-80997859 Website : www.everun.cc Facebook : everunmachinery
 Fax : 0086-532-80993178 Email : info@everun.cc Youtube : everunmachinery